

Tubi tondi elettrosaldati

Tablelle tecniche e tipologie di giacenza

Tabella dei pesi (kg/m)

Diam (mm)	spessori (mm)									
	1.5	2	2.5	3	4	5	6	7	8	9
20	0.68	0.89								
22	0.76	0.99								
25	0.87	1.13								
28	0.98	1.28	1.57							
30	1.05	1.38	1.70	2.00						
32	1.13	1.48	1.82	2.15						
35	1.24	1.63	2.00	2.37						
38	1.35	1.78	2.19	2.59	3.35					
40	1.42	1.87	2.31	2.74	3.55					
42	1.50	1.97	2.44	2.89	3.75					
45	1.61	2.12	2.62	3.11	4.04					
48	1.72	2.27	2.81	3.33	4.34					
50	1.79	2.37	2.93	3.48	4.54					
52	1.87	2.47	3.05	3.63	4.74					
55	1.98	2.61	3.24	3.85	5.03					
57	2.05	2.71	3.36	4.00	5.23					
60	2.16	2.86	3.55	4.22	5.52					
65	2.35	3.11	3.85	4.59	6.02					
70	2.53	3.35	4.16	4.96	6.51	8.01				
76	2.76	3.65	4.53	5.40	7.10	8.75				
80	2.90	3.85	4.78	5.70	7.50	9.25				
83	3.01	4.00	4.96	5.92	7.79	9.62				
89		4.29	5.33	6.36	8.38	10.36	12.28	14.16	15.98	
102		4.93	6.13	7.32	9.67	11.96	14.21	16.40	18.55	
108		5.23	6.50	7.77	10.26	12.70	15.09			
114		5.52	6.87	8.21	10.85	13.44	15.98	18.47	20.91	
127			7.68	9.17	12.13	15.04	17.90	20.72	23.48	
133			8.05	9.62	12.73	15.78	18.79	21.75	24.66	
139.7			8.46	10.11	13.39	16.61	19.78	22.91	25.98	
152				11.02	14.60	18.13	21.60	25.03	28.41	
159				11.54	15.29	18.99	22.64	26.24	29.79	
168				12.21	16.18	20.10	23.97	27.79	31.57	
177.8				12.93	17.14	21.31	25.42	29.49	33.50	
193.7				14.11	18.71	23.27	27.77	32.23	36.64	
219				15.98	21.21	26.39	31.52	36.60	41.63	46.61
244.5					23.72	29.53	35.29	41.00	46.66	52.27
273					26.54	33.05	39.51	45.92	52.28	58.60
323					31.47	39.21	46.91	54.55	62.15	69.69
339.7					33.12	41.27	49.38	57.43	65.44	73.40
355.6					34.68	43.23	51.73	60.18	68.58	76.93
406.4					39.70	49.50	59.25	68.95	78.60	88.20
457.2						55.76	66.76	77.72	88.62	99.48
508						62.02	74.28	86.49	98.65	110.75